

Product Code: LHD

TECHNICAL DATA SHEET

WET GREASE HD

Description

Wet Grease HD is a premium quality, semi-synthetic, water-proof, extreme pressure grease.

Applications

Specifically for slow to medium speed plain and anti-friction bearing applications in marine and other hostile environments. Widely used in the water utilities industry and as a wheel bearing grease for boat trailers and other marine applications.

Advantages

- Water-proof in both salt and fresh water.
- Excellent sealing properties to resist ingress of dirt and moisture.
- Exceptional corrosion resistance

Properties

Wet Grease HD is a slow to medium speed plain, anti-friction, semi-synthetic adhesive grease.

Technical Features

Appearance	Smooth adhesive grease
Colour	Green
NLGI classification	2
Thickener	Lithium soap
Base oil	Semi-synthetic
Base oil viscosity @ 40C (IP71) cSt	1000
Worked penetration (IP50)	265 to 295
Dropping point (IP132) C	185 min.
Oil separation (IP121) %	5 max.
Copper corrosion (IP112)	Pass
Resistance to corrosion Emcor (IP 220)	0:0
Water washout (ASTM D1264) @ 39C %	2.5
Four Ball Weld Load (IP 239) kgs	350
Timken OK load (IP 326) kgs (lbs)	20 (45)
Operating temperature range	-20°C to +140°C

Storage

Keep containers tightly closed in a cool, well-ventilated place.

Presentation

400g Cartridge, 12.5kg Keg

Health & Safety

Avoid Contact with skin and eyes.

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the customer's responsibility to satisfy themselves that each product is fit for the purpose for which they intend to use it, that the actual conditions of use are suitable and that in the light of our continual research and development programme the information relating to each product has not been superseded.